

SOLENOID VALVES FOR HOT WATER & STEAM

1/8" TO 2" NPT NORMALLY CLOSED & NORMALLY OPEN

Teflon Seals



S30 & S31 Direct Acting
1/8", 1/4", 3/8"
Brass or Stainless Steel
0 to 2400 psi Water
0 to 150 psi Steam

S40 Piloted Piston
1/4", 3/8", 1/2"
Brass or Stainless Steel
0 to 300 psi Water
0 to 150 psi Steam

S21..T4 Piloted Diaphragm
3/8", 1/2", 3/4"
Brass
0 to 250 psi Water
0 to 100 psi Steam



S21..T2 Piloted Diaphragm
3/8", 1/2", 3/4"
Brass or Stainless Steel
0 to 2400 psi Water
0 to 150 psi Steam

S21..T4 Piloted Diaphragm
3/8", 1/2", 3/4"
Brass
0 to 250 psi Water
0 to 100 psi Steam

Hot Water & Steam

1/8" TO 2" NPT NORMALLY CLOSED & NORMALLY OPEN

EPR Seals



C9 & C4 Direct Acting
1/8", 1/4", 3/8"
Brass or 316 Stainless Steel
0 to 2030 psi Water
0 to 50 psi Steam



S30 & S31 Direct Acting
1/4", 3/8", 1/2"
Brass or Stainless Steel
0 to 2400 psi Water
0 to 50 psi Steam



S40 Piloted Piston
1/8", 1/4", 3/8"
Brass or Stainless Steel
0 to 3000 psi Water
0 to 50 psi Steam



S21 Piloted Piston
3/8" to 2"
Brass or 316 Stainless Steel
4 to 150 psi Water
4 to 50 psi Steam



S20 Zero Differential
3/8" to 1-1/2"
Brass or 316 Stainless Steel
0 to 140 psi Water
0 to 50 psi Steam



S27 Zero Differential
1" to 2"
Brass or 316 Stainless Steel
0 to 100 psi Water
0 to 50 psi Steam

Other 2- & 3-way Designs:

- Bodies - Stainless Steel, Brass, Polypropylene, Celcon, Nylon, Noryl, others
- Seals - Nitrile, Viton, EPR, Teflon, Rulon, FFKM, Santoprene, others
- Electrical - All Common AC & DC Voltages
- Housings - Conduit, DIN, NEMA 7/9 Explosion Proof, Junction Box, Open Frame Leads
- Manifolds - wide variety of standard products; designed to meet custom applications
- Approvals - UL, CSA, CE, NSF